

**Speeds & Feeds** 

Product Table: Variable Helix End Mills for High Temp Alloys - Ball

Characteristics: 0.8x Length of Cut, 3 Flutes

**Series:** 8481xx-C6, 8724xx-C6

Material	Hardness (HBn)	SFM	Chip Load (IPT) By Cutter Diameter													Depth of Cut	
				0.015	0.031	0.047	0.062	0.078	0.093	0.125	0.187	0.250	0.312	0.375	0.500	Radial	Axial
<b>Stainless Steels</b> : 40x, 41x, 42x, 43x, 44x, 13-8, 15-5, 15-7, 17-4, 17-7	275 - 300	160	Slotting	.00006	.00012	.00019	.00025	.00031	.00037	.00050	.00075	.00100	.00131	.00157	.00209	1x Dia	.4x Dia
	300 - 350	140															
Tool Steels: D, H, M, T, S series	350 - 400	100															
	400 - 425	80	Roughing	.00008	.00016	.00024	.00031	.00040	.00047	.00063	.00095	.00127	.00166	.00200	.00266	.4x Dia	.5x7x Dia
<b>Titanium:</b> All alloys	275 - 300	200															
	300 - 350	125															
	350 - 400	75	Finishing	.00010	.00021	.00031	.00041	.00052	.00062	.00083	.00124	.00166	.00218	.00261	.00349	.1x Dia	.5x8x Dia
	400 - 425	75															
Nickel Alloys: Inconel, Hastelloy, Waspalloy, Monel, Nimonic, Haynes, Discoloy, Incoloy	275 - 300	80															
	300 - 350	60	Max	.00012	.00025	.00037	.00049	.00062	.00074	.00100	.00149	.00199	.00261	.00314	.00418	-	-
	350 - 400	50															
	400 - 425	40															

All posted speed and feed parameters are suggested starting values that may be increased given optimal setup conditions. If less than minimum Axial or Radial DOC values are used, increased feed rates are possible. If greater than maximum Axial or Radial DOC values are used, decreased feed rates may be needed. If you require additional information, Harvey Tool has a team of technical experts available to assist you through even the most challenging applications. Please contact us at 800-645-5609 or Harveytech@harveyperformance.com.

WARNING: Cutting tools may shatter under improper use. Government regulations require use of safety glasses and other appropriate safety equipment in the vicinity of use.