



Speeds & Feeds

**Product Table:** Variable Helix End Mills for High Temp Alloys - Finishers - Corner Radius

**Characteristics:** 1.5x Length of Cut

**Series:** 8723xx-C6, 8801xx-C6, 8905xx-C6

Material	Hardness (HBn)	SFM	Chip Load (IPT) By Cutter Diameter												Depth of Cut		
			0.015	0.031	0.047	0.062	0.078	0.093	0.125	0.187	0.250	0.312	0.375	0.500	Radial	Axial	
Stainless Steels: 40x, 41x, 42x, 43x, 44x, 13-8, 15-5, 15-7, 17-4, 17-7	275 - 300	400	Finishing	.00012	.00024	.00036	.00048	.00060	.00072	.00096	.00144	.00193	.00252	.00303	.00404	< .10x Dia	.5x - 1.5x Dia
	300 - 350	350		.00012	.00024	.00036	.00048	.00060	.00072	.00096	.00144	.00193	.00252	.00303	.00404		
Tool Steels: D , H, M, T, S series	300 - 350	500	Finishing	.00012	.00024	.00036	.00048	.00060	.00072	.00096	.00144	.00193	.00252	.00303	.00404	< .10x Dia	.5x - 1.5x Dia
	350 - 400	250	Finishing	.00009	.00019	.00029	.00038	.00048	.00057	.00077	.00115	.00154	.00202	.00243	.00323	< .10x Dia	.5x - 1.5x Dia
	400 - 540	200	Finishing	.00008	.00016	.00024	.00031	.00039	.00047	.00063	.00094	.00125	.00164	.00197	.00263	< .10x Dia	.5x - 1.5x Dia
Titanium: All alloys	275 - 300	300	Finishing	.00005	.00011	.00016	.00021	.00027	.00032	.00043	.00064	.00085	.00112	.00134	.00179	< .10x Dia	.5x - 1.5x Dia
	300 - 350	200		.00005	.00011	.00016	.00021	.00027	.00032	.00043	.00064	.00085	.00112	.00134	.00179		
	350 - 400	150	Finishing	.00004	.00008	.00013	.00017	.00021	.00025	.00034	.00051	.00068	.00089	.00107	.00143	< .10x Dia	.5x - 1.5x Dia
	400 - 425	100		.00004	.00008	.00013	.00017	.00021	.00025	.00034	.00051	.00068	.00089	.00107	.00143		
Nickel Alloys: Inconel, Hastelloy, Waspalloy, Monel, Nimonic, Haynes, Discoloy, Incoloy	275 - 300	150	Finishing	.00002	.00004	.00007	.00009	.00011	.00013	.00018	.00027	.00036	.00047	.00056	.00075	< .10x Dia	.5x - 1.5x Dia
	300 - 350	100		.00002	.00004	.00007	.00009	.00011	.00013	.00018	.00027	.00036	.00047	.00056	.00075		
	350 - 400	80	Finishing	.00002	.00004	.00005	.00007	.00009	.00011	.00014	.00021	.00029	.00037	.00045	.00060	< .10x Dia	.5x - 1.5x Dia
	400 - 425	60		.00002	.00004	.00005	.00007	.00009	.00011	.00014	.00021	.00029	.00037	.00045	.00060		

**Please note:**  
 All posted speed and feed parameters are suggested starting values that may be increased given optimal setup conditions. If less than minimum Axial or Radial DOC values are used, increased feed rates are possible. If greater than maximum Axial or Radial DOC values are used, decreased feed rates may be needed.  
 If you require additional information, Harvey Tool has a team of technical experts available to assist you through even the most challenging applications. Please contact us at **800-645-5609** or **Harveytech@harveyperformance.com**.  
 WARNING: Cutting tools may shatter under improper use. Government regulations require use of safety glasses and other appropriate safety equipment in the vicinity of use.