

MATERIAL	Hardness: ≤ 28 Rc (≤ 271 HBn)													Depth of Cut			
	SFM	Chip Load (IPT) By Cutter Diameter											Radial			Axial	
		0.062	0.078	0.093	0.125	0.187	0.250	0.312	0.375	0.438	0.500	0.625		0.750	1.000		
ALUMINUM ALLOYS																	
Casting (2xx, 5xx, 7xx, 8xx)	750	.00036	.00045	.00054	.00072	.00113	.00151	.00189	.00227	.00265	.00303	.00378	.00454	.00605	2 Passes	Full Form	
Wrought (1xxx, 2xxx, 3xxx, 5xxx, 6xxx, 7xxx, 8xxx)	1000																
Casting - 3%-5% Si (3xx, A3xx, C3xx, 4xx, A4xx, B4xx)	750																
Casting - 5%-8% Si (3xx, A3xx, C3xx, 4xx, A4xx, B4xx)	700																
Casting - 8%-12% Si (3xx, A3xx, C3xx, 4xx, A4xx, B4xx)	650	.00032	.00041	.00048	.00065	.00102	.00136	.00170	.00204	.00238	.00272	.00340	.00408	.00545	2 Passes	Full Form	
Casting - 12%-16% Si (3xx, A3xx, C3xx, 4xx, A4xx, B4xx)	475																
Wrought - 5%-8% Si (4xxx)	1000																
Wrought - 8%-12% Si (4xxx)	800																
MAGNESIUM ALLOYS	1500	.00036	.00045	.00054	.00072	.00113	.00151	.00189	.00227	.00265	.00303	.00378	.00454	.00605	2 Passes	Full Form	
ZINC ALLOYS	800																
COPPER ALLOYS																	
High Coppers - 90%+ (C1xxxx)	225																
Brass (Copper Zinc alloys, C2xxxx, C3xxxx, C4xxxx, C6400-C69800)	500																
Phosphor Bronzes (Copper Tin alloys, C5xxxx)	225																
Aluminum Bronzes (Copper Aluminum alloys, C60600-C64200)	500	.00029	.00036	.00043	.00058	.00091	.00121	.00151	.00182	.00212	.00242	.00303	.00363	.00484	2 Passes	Full Form	
Silicon Bronzes (Copper Silicon alloys, C64700-C69100)	500																
Copper Nicksels, Nickel Silvers (Copper Nickel alloys, C7xxxx)	225																
Cast Copper Alloys (C83300-C86200, C86400-C87900, C92200-C95800, C97300-C97800, C99400-C99700)	550																



Speeds & Feeds

Product Table: Thread Milling Cutters - Thread Relief Cutter
Series: MTR-XXX

Product notes:

Typical thread reliefs are done before threading to avoid any damage to the threads. Depth of Cut is shown as number of Passes with each pass resulting in a descending stepover.

Chip Loads within table pertain to machining on one side (from tool centerline) of the cutter head. This chart represents a linear feed rate chip load. Since this tool is used in a helical interpolation environment, adjusting the feed rate for a circular motion is needed to avoid deflection and tool breakage. To calculate use the formula:

$$Adj \text{ Internal Circular Feed} = [(Hole \text{ Dia} - \text{Cutter Dia}) / \text{Hole Dia}] \times \text{Linear Feed}$$

General notes:

All posted speed and feed parameters are suggested starting values that may be increased given optimal setup conditions. Chip loads reflect uncoated cutters and may be increased up to 15% if coated. For ferrous materials with hardness ≤ 28 Rc, chip loads can be increased 10%-20%.

If you require additional information, Micro100 has a team of technical experts available to assist you through even the most challenging applications. Please contact us at **800-421-8065** or **micro100tech@harveypformance.com**.

WARNING: Cutting tools may shatter under improper use. Government regulations require use of safety glasses and other appropriate safety equipment in the vicinity of use.

MATERIAL	Hardness: 29-37 Rc (279-344 HBn)													Depth of Cut		
	SFM	Chip Load (IPT) By Cutter Diameter											Radial			Axial
		0.062	0.078	0.093	0.125	0.187	0.250	0.312	0.375	0.438	0.500	0.625		0.750	1.000	
CARBON STEELS																
Free-Machining/Low Carbon steels, 10xx - 1029 & all 10Lxx, 11xx - 1139 & all 11Lxx, 12xx - 1215 & all 12Lxx	600	.00013	.00016	.00020	.00026	.00041	.00055	.00069	.00083	.00097	.00110	.00138	.00166	.00221	3 Passes	Full Form
1030 - 1095, 1140 - 1151, 13xx, 15xx, 20xx, 30xx, 40xx & 4xLxx, 50xx & 5xLxx, 50xxx & 50Lxxx, 51xxx & 51Lxxx, 52xxx & 52Lxxx, 60xx, 80xx, 90xx	200	.00012	.00015	.00018	.00024	.00038	.00050	.00063	.00076	.00088	.00101	.00126	.00151	.00202	3 Passes	Full Form
TOOL STEELS																
A, L, O, P, W series	200	.00012	.00015	.00018	.00024	.00038	.00050	.00063	.00076	.00088	.00101	.00126	.00151	.00202	3 Passes	Full Form
D, H, M, T, S series	150	.00007	.00009	.00011	.00015	.00024	.00032	.00039	.00047	.00055	.00063	.00079	.00095	.00126	3 Passes	Full Form
STAINLESS STEELS																
203 EZ, 303 (all types), 416, 416Se, 416 Plus X, 420F, 420FSe, 430F, 430FSe, 440F, 440FSe	450	.00013	.00016	.00020	.00026	.00041	.00055	.00069	.00083	.00097	.00110	.00138	.00166	.00221	3 Passes	Full Form
201, 202, 203, 205, 301, 302, 304, 304L, 308, 309, 310, 314, 316, 316L, 317, 321, 329, 330, 347, 348, 385, 403, 405, 409, 410, 413, 420, 429, 430, 434, 436, 442, 446, 501, 502	200	.00012	.00015	.00018	.00024	.00038	.00050	.00063	.00076	.00088	.00101	.00126	.00151	.00202	3 Passes	Full Form
414, 431, 440A, 440B, 440C, 13-8, 15-5, 15-7, 17-4, 17-7	150	.00007	.00009	.00011	.00015	.00024	.00032	.00039	.00047	.00055	.00063	.00079	.00095	.00126	3 Passes	Full Form
TITANIUM ALLOYS	150	.00007	.00009	.00011	.00015	.00024	.00032	.00039	.00047	.00055	.00063	.00079	.00095	.00126	3 Passes	Full Form
HIGH TEMP ALLOYS																
Inconel, Hastelloy, Waspaloy, Monel, Nimonic, Haynes, Discology, Incoloy	70	.00007	.00009	.00011	.00015	.00024	.00032	.00039	.00047	.00055	.00063	.00079	.00095	.00126	3 Passes	Full Form

MATERIAL	Hardness: 38-45 Rc (353-421 HBn)													Depth of Cut		
	SFM	Chip Load (IPT) By Cutter Diameter											Radial			Axial
		0.062	0.078	0.093	0.125	0.187	0.250	0.312	0.375	0.438	0.500	0.625		0.750	1.000	
		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
100	.00011	.00013	.00016	.00021	.00033	.00045	.00056	.00067	.00078	.00089	.00111	.00134	.00178	3 Passes	Full Form	
90	.00007	.00008	.00010	.00013	.00021	.00028	.00035	.00042	.00049	.00056	.00070	.00084	.00111	3 Passes	Full Form	
		-	-	-	-	-	-	-	-	-	-	-	-	-	-	
100	.00011	.00013	.00016	.00021	.00033	.00045	.00056	.00067	.00078	.00089	.00111	.00134	.00178	3 Passes	Full Form	
90	.00007	.00008	.00010	.00013	.00021	.00028	.00035	.00042	.00049	.00056	.00070	.00084	.00111	3 Passes	Full Form	
75	.00007	.00008	.00010	.00013	.00021	.00028	.00035	.00042	.00049	.00056	.00070	.00084	.00111	3 Passes	Full Form	
50	.00007	.00008	.00010	.00013	.00021	.00028	.00035	.00042	.00049	.00056	.00070	.00084	.00111	3 Passes	Full Form	