



Speeds & Feeds

Product Table: Engraving Cutters - Tipped Off - Single Ended

Characteristics: Single Ended

Series: RNC-XXX-X, RNC-XXX-XX, RNC-XXX-XXX, RNCM-XXX-X, RSC-XXX-X, RSC-XXX-XX, RSC-XXX-XXX, RSCM-XXX-X, RTC-XXX-X, RTC-XXX-XX, RTC-XXX-XXX, RTCM-XXX-X

Included Angle	Point Offset	RPM	Chip Load (IPT) by Material												Axial DOC	
			Plastics	Non-Ferrous	Iron			Carbon Steels			Stainless Steels		Titanium			High Temp Alloys
			Non-Filled, Glass Filled, Carbon Fiber, G10	Aluminum, Magnesium, Copper Alloys	Cast Iron (< 30 Rc)	Cast Iron (30+ Rc)	Ductile, Malleable	< 29 Rc	30 < 39 Rc	40 < 45 Rc	< 30 Rc	32 < 45 Rc	< 30 Rc	32 < 45 Rc		Inconel, Waspaloy, Monel
30°	0.0025	6000+	.00168	.00112	.00112	.00045	.00056	.00067	.00050	.00028	.00056	.00028	.00056	.00028	.00045	< .010
	0.0050	6000+	.00210	.00140	.00140	.00056	.00070	.00084	.00063	.00035	.00070	.00035	.00070	.00035	.00056	< .010
	0.0075	6000+	.00210	.00140	.00140	.00056	.00070	.00084	.00063	.00035	.00070	.00035	.00070	.00035	.00056	< .010
	0.0100	6000+	.00210	.00140	.00140	.00056	.00070	.00084	.00063	.00035	.00070	.00035	.00070	.00035	.00056	< .010
	0.0150	6000+	.00210	.00140	.00140	.00056	.00070	.00084	.00063	.00035	.00070	.00035	.00070	.00035	.00056	< .011
60°	0.0025	6000+	.00228	.00152	.00152	.00061	.00076	.00091	.00068	.00038	.00076	.00038	.00076	.00038	.00061	< .011
	0.0050	6000+	.00300	.00200	.00200	.00080	.00100	.00120	.00090	.00050	.00100	.00050	.00100	.00050	.00080	< .010
	0.0075	6000+	.00300	.00200	.00200	.00080	.00100	.00120	.00090	.00050	.00100	.00050	.00100	.00050	.00080	< .010
	0.0100	6000+	.00300	.00200	.00200	.00080	.00100	.00120	.00090	.00050	.00100	.00050	.00100	.00050	.00080	< .010
	0.0150	6000+	.00300	.00200	.00200	.00080	.00100	.00120	.00090	.00050	.00100	.00050	.00100	.00050	.00080	< .010
90°	0.0025	6000+	.00264	.00176	.00176	.00070	.00088	.00106	.00079	.00044	.00088	.00044	.00088	.00044	.00070	< .010
	0.0050	6000+	.00330	.00220	.00220	.00088	.00110	.00132	.00099	.00055	.00110	.00055	.00110	.00055	.00088	< .010
	0.0075	6000+	.00330	.00220	.00220	.00088	.00110	.00132	.00099	.00055	.00110	.00055	.00110	.00055	.00088	< .010
	0.0100	6000+	.00330	.00220	.00220	.00088	.00110	.00132	.00099	.00055	.00110	.00055	.00110	.00055	.00088	< .010
	0.0150	6000+	.00330	.00220	.00220	.00088	.00110	.00132	.00099	.00055	.00110	.00055	.00110	.00055	.00088	< .010

Please note:

All posted speed and feed parameters are suggested starting values that may be increased given optimal setup conditions (minimal runout is required for best results).

Suggested speed is 6000 rpm or more. Choose an rpm value that creates the least amount of internal machine vibration. In many cases, a speed increaser is helpful.

Posted chip loads reflect axial depths of cut up to .009. For depths of cut = .010"-.015", reduce posted chip loads by 20%. For depths of cut = .016"-.020", reduce posted chip loads by 30%.

Posted chip loads reflect uncoated cutters. Coating is better suited to prolong tool life rather than decrease cycle times.

Posted chip loads reflect HORIZONTAL milling conditions. For VERTICAL plunge milling to depth, reduce posted chip loads by 50% (ramping is preferred to maintain tip integrity).

If you require additional information, Micro100 has a team of technical experts available to assist you through even the most challenging applications. Please contact us at 800-421-8065 or micro100tech@harveypformance.com.

WARNING: Cutting tools may shatter under improper use. Government regulations require use of safety glasses and other appropriate safety equipment in the vicinity of use.