

Product Notes:
Due to a varying diameter, an Effective Cutter Diameter is needed for Chip Load selection and RPM calculation:
Effective Cutter Diameter = (Major Diameter + Minor Diameter)/2.
Or consider the actual diameter along the angle that is engaged with the workpiece.

Depth of Cut is shown as number of Passes with each pass resulting in a descending stepover

Chip Loads are given 3 ways:
Traditional Edge Break of .010"-.015"
Full Chamfer engagement for cutters with angles GREATER than 25° per side (50° included)
Full Chamfer engagement for cutters with angles LESS than 25° per side (50° included)

Chip Loads within table pertain to machining on one side of workpiece.
For machining on two sides, reduce Chip Loads to 60%-80% depending on contact length and finish
For vertical plunging, reduce Chip Loads to 40%-50% depending on finish

Material Guide		Hardness	SFM	Operation	Chip Load (IPT) By Effective Cutter Diameter												Depth of Cut Passes	
					1/64	1/32	3/64	1/16	5/64	3/32	1/8	3/16	1/4	5/16	3/8	1/2		
Carbon Steel	10XX, 11XX, 12XX, 12LXX, ASTM A27, ASTM A36	29-37 Rc (279-344 HBn)	600	Edge Break	.00009	.00018	.00027	.00035	.00044	.00053	.00071	.00106	.00142	.00177	.00213	.00284	1	
				Full Chamfer (≥ 25°)	.00007	.00015	.00022	.00029	.00037	.00044	.00059	.00088	.00118	.00147	.00177	.00236	3	
				Full Chamfer (< 25°)	.00005	.00011	.00017	.00022	.00028	.00033	.00044	.00066	.00089	.00111	.00133	.00177	4	
Low Alloy Steel	13XX, 41XX, 43XX, 51XX, 86XX, 93XX	29-37 Rc (279-344 HBn)	200	Edge Break	.00008	.00016	.00024	.00032	.00040	.00048	.00065	.00097	.00130	.00162	.00194	.00259	1	
				Full Chamfer (≥ 25°)	.00006	.00013	.00020	.00027	.00034	.00040	.00054	.00081	.00108	.00135	.00162	.00216	3	
				Full Chamfer (< 25°)	.00005	.00010	.00015	.00020	.00025	.00030	.00041	.00061	.00081	.00101	.00122	.00162	4	
Tool Steel	A, L, O, P, W series	29-37 Rc (279-344 HBn)	200	Edge Break	.00008	.00016	.00024	.00032	.00040	.00048	.00065	.00097	.00130	.00162	.00194	.00259	1	
				Full Chamfer (≥ 25°)	.00006	.00013	.00020	.00027	.00034	.00040	.00054	.00081	.00108	.00135	.00162	.00216	3	
				Full Chamfer (< 25°)	.00005	.00010	.00015	.00020	.00025	.00030	.00041	.00061	.00081	.00101	.00122	.00162	4	
		38-45 Rc (353-421 HBn)	100	Edge Break	.00008	.00016	.00024	.00032	.00040	.00048	.00065	.00097	.00130	.00162	.00194	.00259	1	
				Full Chamfer (≥ 25°)	.00006	.00013	.00020	.00027	.00034	.00040	.00054	.00081	.00108	.00135	.00162	.00216	4	
				Full Chamfer (< 25°)	.00005	.00010	.00015	.00020	.00025	.00030	.00041	.00061	.00081	.00101	.00122	.00162	5	
	D, H, M, T, S series	29-37 Rc (279-344 HBn)	150	Edge Break	.00005	.00010	.00015	.00020	.00025	.00030	.00041	.00061	.00081	.00101	.00122	.00162	1	
				Full Chamfer (≥ 25°)	.00004	.00008	.00013	.00017	.00021	.00025	.00034	.00050	.00068	.00084	.00101	.00135	4	
				Full Chamfer (< 25°)	.00003	.00006	.00010	.00013	.00016	.00019	.00025	.00038	.00051	.00063	.00076	.00101	5	
		38-45 Rc (353-421 HBn)	75	Edge Break	.00005	.00010	.00015	.00020	.00025	.00030	.00041	.00061	.00081	.00101	.00122	.00162	1	
				Full Chamfer (≥ 25°)	.00004	.00008	.00013	.00017	.00021	.00025	.00034	.00050	.00068	.00084	.00101	.00135	4	
				Full Chamfer (< 25°)	.00003	.00006	.00010	.00013	.00016	.00019	.00025	.00038	.00051	.00063	.00076	.00101	5	
Austenitic Stainless Steel	Nitronic 50, Nitronic 60, 301, 303, 304, 304L, Incoloy 27-7MO, 316, 316L, 321, 347	29-37 Rc (279-344 HBn)	450	Edge Break	.00009	.00018	.00027	.00035	.00044	.00053	.00071	.00106	.00142	.00177	.00213	.00284	1	
				Full Chamfer (≥ 25°)	.00007	.00015	.00022	.00029	.00037	.00044	.00059	.00088	.00118	.00147	.00177	.00236	3	
				Full Chamfer (< 25°)	.00005	.00011	.00017	.00022	.00028	.00033	.00044	.00066	.00089	.00111	.00133	.00177	4	
Martensitic & Ferritic Stainless Steel	403, 410, 416, 420, 440, 430, 446	29-37 Rc (279-344 HBn)	200	Edge Break	.00008	.00016	.00024	.00032	.00040	.00048	.00065	.00097	.00130	.00162	.00194	.00259	1	
				Full Chamfer (≥ 25°)	.00006	.00013	.00020	.00027	.00034	.00040	.00054	.00081	.00108	.00135	.00162	.00216	3	
				Full Chamfer (< 25°)	.00005	.00010	.00015	.00020	.00025	.00030	.00041	.00061	.00081	.00101	.00122	.00162	4	
		38-45 Rc (353-421 HBn)	100	Edge Break	.00008	.00016	.00024	.00032	.00040	.00048	.00065	.00097	.00130	.00162	.00194	.00259	1	
				Full Chamfer (≥ 25°)	.00006	.00013	.00020	.00027	.00034	.00040	.00054	.00081	.00108	.00135	.00162	.00216	4	
				Full Chamfer (< 25°)	.00005	.00010	.00015	.00020	.00025	.00030	.00041	.00061	.00081	.00101	.00122	.00162	5	
PH Stainless Steel	15-5, 17-4, Carpenter 450, Carpenter 465	29-37 Rc (279-344 HBn)	150	Edge Break	.00005	.00010	.00015	.00020	.00025	.00030	.00041	.00061	.00081	.00101	.00122	.00162	1	
				Full Chamfer (≥ 25°)	.00004	.00008	.00013	.00017	.00021	.00025	.00034	.00050	.00068	.00084	.00101	.00135	3	
				Full Chamfer (< 25°)	.00003	.00006	.00010	.00013	.00016	.00019	.00025	.00038	.00051	.00063	.00076	.00101	4	
		38-45 Rc (353-421 HBn)	90	Edge Break	.00005	.00010	.00015	.00020	.00025	.00030	.00041	.00061	.00081	.00101	.00122	.00162	1	
				Full Chamfer (≥ 25°)	.00004	.00008	.00013	.00017	.00021	.00025	.00034	.00050	.00068	.00084	.00101	.00135	4	
				Full Chamfer (< 25°)	.00003	.00006	.00010	.00013	.00016	.00019	.00025	.00038	.00051	.00063	.00076	.00101	5	
Nickel Alloy	Hastelloy C-22, Inconel 625, Waspaloy, René 41, Inconel 718, Incoloy 20	29-37 Rc (279-344 HBn)	70	Edge Break	.00005	.00010	.00015	.00020	.00025	.00030	.00041	.00061	.00081	.00101	.00122	.00162	1	
				Full Chamfer (≥ 25°)	.00004	.00008	.00013	.00017	.00021	.00025	.00034	.00050	.00068	.00084	.00101	.00135	3	
				Full Chamfer (< 25°)	.00003	.00006	.00010	.00013	.00016	.00019	.00025	.00038	.00051	.00063	.00076	.00101	4	
		38-45 Rc (353-421 HBn)	50	Edge Break	.00005	.00010	.00015	.00020	.00025	.00030	.00041	.00061	.00081	.00101	.00122	.00162	1	
				Full Chamfer (≥ 25°)	.00004	.00008	.00013	.00017	.00021	.00025	.00034	.00050	.00068	.00084	.00101	.00135	4	
				Full Chamfer (< 25°)	.00003	.00006	.00010	.00013	.00016	.00019	.00025	.00038	.00051	.00063	.00076	.00101	5	
Titanium Alloy	Ti 3Al-2.5V, Ti 6Al-4V, Ti 10V-2Fe-3Al	29-37 Rc (279-344 HBn)	150	Edge Break	.00005	.00010	.00015	.00020	.00025	.00030	.00041	.00061	.00081	.00101	.00122	.00162	1	
				Full Chamfer (≥ 25°)	.00004	.00008	.00013	.00017	.00021	.00025	.00034	.00050	.00068	.00084	.00101	.00135	3	
				Full Chamfer (< 25°)	.00003	.00006	.00010	.00013	.00016	.00019	.00025	.00038	.00051	.00063	.00076	.00101	4	
		38-45 Rc (353-421 HBn)	75	Edge Break	.00005	.00010	.00015	.00020	.00025	.00030	.00041	.00061	.00081	.00101	.00122	.00162	1	
				Full Chamfer (≥ 25°)	.00004	.00008	.00013	.00017	.00021	.00025	.00034	.00050	.00068	.00084	.00101	.00135	4	
				Full Chamfer (< 25°)	.00003	.00006	.00010	.00013	.00016	.00019	.00025	.00038	.00051	.00063	.00076	.00101	5	
Wrought Aluminum Alloy	2014, 5062, 6061, 7050, 7075, 7475	≤ 28 Rc (≤ 271 HBn)	1000	Edge Break	.00023	.00047	.00071	.00093	.00117	.00140	.00188	.00281	.00375	.00468	.00563	.00750	1	
				Full Chamfer (≥ 25°)	.00019	.00039	.00059	.00078	.00098	.00116	.00156	.00234	.00313	.00390	.00469	.00625	2	
				Full Chamfer (< 25°)	.00014	.00029	.00044	.00058	.00073	.00087	.00117	.00175	.00234	.00293	.00352	.00469	3	
		5% - 8% Si (4XXX)	1000	Edge Break	.00023	.00047	.00071	.00093	.00117	.00140	.00188	.00281	.00375	.00468	.00563	.00750	1	
				Full Chamfer (≥ 25°)	.00019	.00039	.00059	.00078	.00098	.00116	.00156	.00234	.00313	.00390	.00469	.00625	2	
				Full Chamfer (< 25°)	.00014	.00029	.00044	.00058	.00073	.00087	.00117	.00175	.00234	.00293	.00352	.00469	3	
Cast Aluminum Alloy	319.0, 328.0, 355.0, 360.0, 380.0, 383.0, 390.0, 520.0, 535.0	750		Edge Break	.00020	.00042	.00063	.00084	.00105	.00126	.00169	.00252	.00338	.00421	.00506	.00675	1	
				Full Chamfer (≥ 25°)	.00017	.00035	.00053	.00070	.00088	.00105	.00141	.00210	.00281	.00351	.00422	.00563	2	
				Full Chamfer (< 25°)	.00013	.00026	.00040	.00052	.00066	.00078	.00105	.00158	.00211	.00263	.00316	.00422	3	
		3% - 5% Si (3XX, A3XX, C3XX, 4XX, A4XX, B4XX)	750		Edge Break	.00020	.00042	.00063	.00084	.00105	.00126	.00169	.00252	.00338	.00421	.00506	.00675	1
					Full Chamfer (≥ 25°)	.00017	.00035	.00053	.00070	.00088	.00105	.00141	.00210	.00281	.00351	.00422	.00563	2
					Full Chamfer (< 25°)	.00013	.00026	.00040	.00052	.00066	.00078	.00105	.00158	.00211	.00263	.00316	.00422	3
5% - 8% Si (3XX, A3XX, C3XX, 4XX, A4XX, B4XX)	≤ 28 Rc (≤ 271 HBn)	700		Full Chamfer (≥ 25°)	.00017	.00035	.00053	.00070	.00088	.00105	.00141	.00210	.00281	.00351	.00422	.00563	2	
				650														
																	475	
Copper Alloy	Cu-ETP, CuBe2, CuZn30, CuZn36Pb3, CuZn10, CuSn5	≤ 28 Rc (≤ 271 HBn)	225-500	Edge Break	.00018	.00037	.00056	.00074	.00094	.00112	.00150	.00224	.00300	.00374	.00450	.00600		
				Full Chamfer (≥ 25°)	.00015	.00031	.00047	.00062	.00078	.00093	.00125	.00187	.00250	.00312	.00375	.00500	2	
				Full Chamfer (< 25°)	.00011	.00023	.00035	.00047	.00059	.00070	.00094	.00140	.00188	.00234	.00281	.00375	3	
Magnesium Alloys		≤ 28 Rc (≤ 271 HBn)	1500	Edge Break	.00023	.00047	.00071	.00093	.00117	.00140	.00188	.00281	.00375	.00468	.00563	.00750	1	
				Full Chamfer (≥ 25°)	.00019	.00039	.00059	.00078	.00098	.00116	.00156	.00234	.00313	.00390	.00469	.00625	2	
Zinc Alloys		≤ 28 Rc (≤ 271 HBn)	800	Full Chamfer (< 25°)	.00014	.00029	.00044	.00058	.00073	.00087	.00117	.00175	.00234	.00293	.00352	.00469	3	