

Speeds & Feeds

Product Table: End Mills for Steels & High Temp Alloys - Square - 5 Flute - Stub & Standard

End Mills for Steels & High Temp Alloys - Square - 4 & 6 Flute Characteristics: 1x, 2x Length of Cut, 4, 5 & 6 Flutes

Series: ASM-XXX-X, EMH-XXX-XX, EMHM-XXX-X, VHM-XXX-X

Material	Hardness (HBn)	SFM	Chip Load (IPT) By Cutter Diameter														Depth of Cut	
				0.015	0.031	0.047	0.062	0.078	0.093	0.125	0.187	0.250	0.312	0.375	0.500	Radial	Axial	
Tool Steels: D, H, M, T, S series	350 - 400	100	Slotting	.00005 .00010														
	400 - 425	80			.00016	.00021	.00026	.00031	.00042	.00063	.00084	.00110	.00132	.00176	1x Dia	.4x Dia		
Stainless Steels: 40x, 41x, 42x, 43x, 44x, 13-8, 15-5, 15-7, 17-4, 17-7	275 - 300	160																
	300 - 350	140		.000.		.00020	.00027	.00034	.00040	.00054	.00081	.00108	.00142	.00170	.00227	.4x Dia	.5x7x Dia	
Titanium: All alloys	275 - 300	200	Roughing		.00013													
	300 - 350	125																
	350 - 400	75	Finishing	.00008		.00026	.00035	.00044	.00052	.00070	.00105	.00140	.00184	.00221	.00295	.1x Dia	.5x - 1x Dia	
	400 - 425	75			.00017													
Nickel Alloys: Inconel, Hastelloy, Waspalloy, Monel, Nimonic, Haynes, Discoloy, Incoloy	275 - 300	80																
	300 - 350	60	Max	.00010 .00021		.00032	.00042	.00053	.00063	.00085	.00127	.00170	.00223	.00268	.00357	-	-	
	350 - 400	50			.00021													
	400 - 425	40																

Please note:

All posted speed and feed parameters are suggested starting values that may be increased given optimal setup conditions. If less than minimum Axial or Radial DOC values are used, increased feed rates are possible. If greater than maximum Axial or Radial DOC values are used, decreased feed rates may be needed. If you require additional information, Micro100 has a team of technical experts available to assist you through even the most challenging applications. Please contact us at 800-421-8065 or micro100tech@harveyperformance.com.

WARNING: Cutting tools may shatter under improper use. Government regulations require use of safety glasses and other appropriate safety equipment in the vicinity of use.