



Speeds & Feeds

Product Table: Variable Helix End Mills for Free Machining Steels - Finishers - Square
Characteristics: 3x Length of Cut
Series: 9219xx-C3, 9678xx-C3, 9679xx-C3

Material	Hardness (HBn)	SFM	Chip Load (IPT) By Cutter Diameter												Depth of Cut		
			0.015	0.031	0.047	0.062	0.078	0.093	0.125	0.187	0.250	0.312	0.375	0.500	Radial	Axial	
CARBON STEELS 10xx - 1030, 10Lxx, 11xx - 1140, 11Lxx, 12xx - 1215, 12Lxx	100-125	500	Finishing	.00023	.00047	.00071	.00093	.00117	.00140	.00188	.00281	.00375	.00491	.00591	.00788	< .10x Dia	.5x - 3x Dia
	125-150	425															
	150-175	400															
175-200	375																
200-225	350																
STAINLESS STEELS 203 EZ, 303 (all types), 416, 416 Se, 416 Plus X., 420 F, 420 F Se																	

Please note:
 All posted speed and feed parameters are suggested starting values that may be increased given optimal setup conditions. If less than minimum Axial or Radial DOC values are used, increased feed rates are possible.
 If you require additional information, Harvey Tool has a team of technical experts available to assist you through even the most challenging applications. Please contact us at **800-645-5609** or **Harveytech@harveyperformance.com**.
 WARNING: Cutting tools may shatter under improper use. Government regulations require use of safety glasses and other appropriate safety equipment in the vicinity of use.