



Speeds & Feeds

Product Table: Miniature End Mills - Ball - Deburring End Mill - Stub Length of Cut

Series: 6978xx

Material	SFM	Chip Load (IPT) By Cutter Diameter								
		0.015	0.031	0.047	0.062	0.078	0.093	0.125	0.187	0.250
Non-Ferrous Alloys Aluminum, Magnesium, Zinc & Copper Alloys	800	.00009	.00019	.00034	.00045	.00057	.00068	.00091	.00136	.00182
Ferrous Alloys Carbon, Stainless & Tool Steels	200	.00008	.00017	.00031	.00041	.00051	.00061	.00083	.00123	.00165
High Temp Alloys Titanium, Inconel & Nickel Based Alloys	100	.00007	.00015	.00028	.00037	.00046	.00055	.00074	.00111	.00149

Please note:

All posted speed and feed parameters are suggested starting values that may be increased given optimal setup conditions.

Speed and feed calculations should be made in the traditional manner with 2 adjustments:

1. In cases that involve a angled cutter diameter (like a cone shape), the EFFECTIVE cutter diameter should be used; that is, the specific diameter within the angled form that directly contacts the burr.
2. Burs possess right and left hand flutes. Feed calculations should be made using the number of right hand flutes only.

Posted chip loads reflect uncoated cutters. Coating is better suited to prolong tool life rather than decrease cycle times.

Axial and radial depths of cut are not posted as deburring is typically done in one pass.

Since miniscule material is being removed, chip load is not as closely connected to the workpiece material as is seen in traditional machining, allowing minimal material buckets.

If you require additional information, Harvey Tool has a team of technical experts available to assist you through even the most challenging applications. Please contact us at **800-645-5609** or Harveytech@harveyperformance.com.

WARNING: Cutting tools may shatter under improper use. Government regulations require use of safety glasses and other appropriate safety equipment in the vicinity of use.