



Speeds & Feeds

Product Table: Miniature End Mills - Ball - Long Reach, Long Flute
Characteristics: 8x, 10x, 13x, 14x, 16x Reach Multiple, 5x, 6x, 7x, 8x Length of Cut, 3 Flutes
Series: 102xx, 103xx, 138xx, 148xx, 7240xx, 7504xx, 8033xx, 8035xx

Please note:

All posted speed and feed parameters are suggested starting values that may be increased given optimal setup conditions. Chip loads reflect uncoated cutters and may be increased 10%-20% if coated. For ferrous materials with hardness ≤ 28 Rc, chip loads can be increased 10%-20%.

If you require additional information, Harvey Tool has a team of technical experts available to assist you through even the most challenging applications. Please contact us at 800-645-5609 or harveytech@harveyperformance.com.

WARNING: Cutting tools may shatter under improper use. Government regulations require use of safety glasses and other appropriate safety equipment in the vicinity of use.

Table with columns: MATERIAL, SFM, Chip Load (IPT) by Dia (0.015, 0.031, 0.047), Depth of Cut (Radial, Axial), Chip Load (IPT) by Cutter Dia (0.062, 0.078, 0.093, 0.125, 0.187, 0.250, 0.375, 0.500), Depth of Cut (Radial, Axial). Rows include Aluminum Alloys, Magnesium Alloys, Zinc Alloys, Copper Alloys, and Cast Copper Alloys.

Table with columns: MATERIAL, SFM, Chip Load (IPT) by Dia (0.015, 0.031, 0.047), Depth of Cut (Radial, Axial), Chip Load (IPT) by Cutter Dia (0.062, 0.078, 0.093, 0.125, 0.187, 0.250, 0.375, 0.500), Depth of Cut (Radial, Axial). Rows include Carbon Steels, Stainless Steels, Tool Steels, Titanium Alloys, and High Temp Alloys.

Table with columns: MATERIAL, SFM, Chip Load (IPT) by Dia (0.015, 0.031, 0.047), Depth of Cut (Radial, Axial), Chip Load (IPT) by Cutter Dia (0.062, 0.078, 0.093, 0.125, 0.187, 0.250, 0.375, 0.500), Depth of Cut (Radial, Axial). Rows include Carbon Steels, Stainless Steels, Tool Steels, Titanium Alloys, and High Temp Alloys.